


400 SERIES AWNING WINDOWS

Table of Basic Awning Unit Sizes Scale 1/8" = 1'-0" (1:96)

Unit Dimension	2'-0 1/8" (613)	2'-4 3/8" (721)	2'-7 1/2" (800)	2'-11 15/16" (913)	3'-4 13/16" (1037)	4'-0" (1219)	4'-4 13/16" (1341)	4'-11 7/8" (1521)	5'-4 13/16" (1646)	5'-11 7/8" (1826)
Minimum Rough Opening	2'-0 5/8" (625)	2'-4 7/8" (733)	2'-8" (813)	3'-0 1/2" (927)	3'-5 3/8" (1051)	4'-0 1/2" (1232)	4'-5 3/8" (1356)	5'-0 3/8" (1534)	5'-5 3/8" (1660)	6'-0 3/8" (1838)
Unobstructed Glass	19 5/16" (491)	23 9/16" (598)	27 1/8" (689)	31 1/8" (791)	36" (914)	43 3/16" (1097)	48" (1219)	55 1/16" (1399)	60" (1524)	67 1/16" (1703)
1'-5" (432)										
1'-8 1/2" (521)										
2'-0 1/8" (613)										
2'-4 3/8" (721)										
2'-7 1/2" (800)										
2'-11 15/16" (913)										
3'-4 3/4" (1035)										
4'-0" (1219)										



Venting Stationary

Venting Configuration

Andersen® art glass panels not available for these units.

‡ Andersen® art glass panels are available for these units by special order only. Contact your Andersen® supplier. Panels are available for all other units on this page, except where noted, through normal ordering process. Visit andersenwindows.com/artglass for patterns.

- **Rough opening dimensions may need to be increased to allow for use of building wraps, flashing, sill panning, brackets, fasteners or other items.**
- Dashed lines on size tables indicate hinging (also available as stationary units).
- Stationary units are available as venting units by special order. Some restrictions may apply. Contact your local Andersen® Supplier.
- "Unit Dimension" always refers to outside frame to frame dimension.
- Dimensions in parentheses are in millimeters.
- When ordering, be sure to specify color desired: White, Sandtone, Terratone® or Forest Green.

* The maximum clear opening of the A335 unit in normal operation is 6 1/8". The operator can be detached from the sash of the A335 unit to obtain a clear opening of 26 5/8".

400 SERIES AWNING WINDOWS

Table of Basic Awning Unit Sizes Scale 1/8" = 1'-0" (1:96)

Unit Dimension	4'-0" (1219)	4'-8 1/2" (1435)	5'-2 3/4" (1594)	5'-11 5/8" (1819)	5'-11 7/8" (1826)	7'-0 5/8" (2149)
Minimum Rough Opening	4'-0 1/2" (1232)	4'-9" (1448)	5'-3 1/4" (1607)	6'-0 1/8" (1832)	6'-0 3/8" (1838)	7'-1 1/8" (2162)
Unobstructed Glass*	19 5/16" (491)	23 9/16" (598)	27 1/8" (689)	31 1/8" (791)	19 5/16" (491)	23 9/16" (598)
1'-5" (432)	 AR221	 AR2251	 AR2281	 AR231	 AR321	 AR3251
1'-8 1/2" (521)	 AN221	 AN2251	 AN2281	 AN231	 AN321	 AN3251
2'-0 1/8" (613)	 A221	 A2251	 A2281	 A231	 A321	 A3251
2'-4 3/8" (721)	 AW221	 AW2251	 AW2281	 AW231	 AW321	 AW3251
2'-7 1/2" (800)	 AX2251	 AX2281	 AX231			
2'-11 15/16" (913)		 AXW2281	 AXW231			

Unit Dimension	2'-0 1/8" (613)	2'-11 15/16" (913)	2'-11 15/16" (913)	2'-11 15/16" (913)	3'-4 13/16" (1037)	4'-0" (1219)
Minimum Rough Opening	2'-0 5/8" (625)	3'-0 1/2" (927)	3'-0 1/2" (927)	3'-0 1/2" (927)	3'-5 3/8" (1051)	4'-0 1/2" (1232)
4'-0" (1219)	 A212 (A21/A21)	 A312 (A31/A31)				
4'-11 13/16" (1519)		 PA3050 (AXW31/A31)		 PA3550 (AXW351/A351)		
5'-11 7/8" (1826)	 A213 (A21/A21/A21)	 PA3060 (AP32V/A31)	 AXW312* (AXW31/AXW31)	 A313 (A31/A31/A31)	 PA3560 (AP352V/A351)	 PA4060 (AP42V/A41)

* Unit dimension height for **AXW312** is 5'-11 5/8"

* Unobstructed glass width is for single sash only.

- **Rough opening dimensions may need to be increased to allow for use of building wraps, flashing, sill panning, brackets, fasteners or other items.**
- Dashed lines on size tables indicate hinging (also available as stationary units).
- Stationary units are available as venting units by special order. Some restrictions may apply. Contact your local Andersen® Supplier.
- "Unit Dimension" always refers to outside frame to frame dimension.
- Dimensions in parentheses are in millimeters.
- When ordering, be sure to specify color desired: White, Sandtone, Terratone® or Forest Green.

