

400 SERIES CASEMENT WINDOWS

Table of Basic Casement Unit Sizes Scale 1/8" = 1'-0" (1:96)

Unit Dimension	1'-5"	1'-8 1/2"	2'-0 1/8"	2'-4 3/8"	2'-7 1/2"	2'-11 15/16"	2'-9 3/4"	3'-4 3/4"	4'-0"	4'-8 1/2"
Minimum Rough Opening	1'-5 1/2" (445)	1'-9" (533)	2'-0 5/8" (625)	2'-4 7/8" (733)	2'-8" (813)	3'-0 1/2" (927)	2'-10 1/4" (870)	3'-5 1/4" (1048)	4'-0 1/2" (1232)	4'-9" (1448)
Unobstructed Glass*	12 5/8" (321)	16 1/8" (410)	19 3/4" (502)	24" (610)	27 1/8" (689)	31 9/16" (802)	12 5/8" (321)	16 1/8" (410)	19 3/4" (502)	24" (610)
Unobstructed Glass Transom Units Only	12 3/16" (310)	15 11/16" (398)	19 5/16" (491)	23 9/16" (599)	26 11/16" (678)	31 1/8" (791)	28 15/16" (735)	35 15/16" (913)	43 3/16" (1097)	51 11/16" (1313)
1'-0"	 CTR1510 ‡	 CTR1810 ‡	 CTR2010 ‡	 CTR2410 ‡	 CTR2810 ‡	 CTR3010 ‡	 CTR2910 ‡	 CTR3410 ‡	 CTR4010 ‡	 CTR4810 ‡
1'-0"	 CTR1510 ‡	 CTR1810 ‡	 CTR2010 ‡	 CTR2410 ‡	 CTR2810 ‡	 CTR3010 ‡	 CTR2910 ‡	 CTR3410 ‡	 CTR4010 ‡	 CTR4810 ‡
2'-0 1/8"	 CR12	 CN12	 C12	 CW12				 CN22	 C22	 CW22
2'-4 3/8"	 CR125	 CN125	 C125	 CW125	 CX125			 CN225	 C225	 CW225
2'-11 15/16"	 CR13	 CN13	 C13	 CW13	 CX13	 CXW13	 CR23	 CN23	 C23	 CW23
3'-4 13/16"	 CR135	 CN135	 C135	 CW135 †	 CX135** †	 CXW135 †	 CR235	 CN235	 C235	 CW235 †
4'-0"	 CR14	 CN14	 C14	 CW14 †	 CX14 †	 CXW14 †	 CR24	 CN24	 C24	 CW24 †
4'-4 13/16"	 CR145	 CN145	 C145	 CW145 †	 CX145 †	 CXW145 †	 CR245	 CN245	 C245	 CW245 †
4'-11 7/8"	 CR15	 CN15	 C15	 CW15 †	 CX15 †	 CXW15** †	 CR25	 CN25	 C25	 CW25 †
5'-4 13/16"	 CR155	 CN155	 C155	 CW155 †	 CX155 †	 CXW155** †	 CR255	 CN255	 C255	 CW255 †
5'-11 7/8"	 CR16	 CN16	 C16	 CW16 †	 CX16 †	 CXW16** †	 CR26	 CN26	 C26	 CW26 †

CTR (transom)
units are
non-venting.

* "Unobstructed Glass" measurement is for single sash only.

** These units have straight arm operators, see opening specifications.

† CW series units (except CW2, CW25 and CW3 height) open to 20" clear opening width using sill hinge control bracket. Bracket can be pivoted allowing for cleaning position.

CW series units are also available with a 22" clear opening width.

‡ Andersen® art glass panels are available for these units by special order only. Contact your Andersen® supplier. Panels are available for all other units on this page through normal ordering process. Visit andersenwindows.com/artglass for patterns.

◆ These units meet or exceed the following dimensions: Clear Openable Area of 5.7 sq. ft., Clear Openable Width of 20" and Clear Openable Height of 24", when appropriate hardware (straight arm or split arm) is specified.

• Casement transom units (CTR) may be rotated to be used as a casement or awning sidelight.

• Rough opening dimensions may need to be increased to allow for use of building wraps, flashing, sill panning, brackets, fasteners or other items.







• "Unit Dimension" always refers to outside frame to frame dimension.


• Dimensions in parentheses are in millimeters.

• When ordering, be sure to specify color desired: White, Sandtone, Terratone® or Forest Green.

400 SERIES CASEMENT WINDOWS

Table of Basic Casement Unit Sizes Scale $\frac{1}{8}" = 1'-0"$ (1:96)

5'-2 $\frac{3}{4}"$ (1594)	5'-11 $\frac{5}{8}"$ (1819)	5'-1" (1549)	5'-11 $\frac{7}{8}"$ (1826)	7'-0 $\frac{5}{8}"$ (2149)
5'-3 $\frac{1}{4}"$ (1607)	6'-0 $\frac{1}{8}"$ (1832)	5'-1 $\frac{1}{2}"$ (1562)	6'-0 $\frac{3}{8}"$ (1838)	7'-1 $\frac{1}{8}"$ (2162)
27 $\frac{1}{8}"$ (689)	31 $\frac{9}{16}"$ (802)	16 $\frac{1}{8}"$ (410)	19 $\frac{3}{4}"$ (502)	24" (610)
57 $\frac{15}{16}"$ (1472)	66 $\frac{13}{16}"$ (1697)	56 $\frac{3}{16}"$ (1427)	67 $\frac{1}{16}"$ (1703)	79 $\frac{13}{16}"$ (2027)
 CTR5210 ‡	 CTR5110 ‡	 CTR5110 ‡	 CTR6010 ‡	 CTR7010 ‡
 CTR22810	 CTR23010	 CTR31810	 CTR32010	 CTR32410
		 CN32	 C32	 CW32
		 CN325	 C325	 CW325
 CX23	 CXW23	 CN33	 C33	 CW33
 CX235** ♦	 CXW235 ♦	 CN335	 C335	 CW335† ♦
 CX24 ♦	 CXW24 ♦	 CN34	 C34	 CW34† ♦
 CX245 ♦	 CXW245 ♦	 CN345	 C345	 CW345† ♦
 CX25 ♦	 CXW25** ♦	 CN35	 C35	 CW35† ♦



Venting Configuration

Hinging shown on size table is standard.
Specify left, right or stationary, as viewed
from the outside. For other hinging of
multiple units, contact your local supplier.

NOTE: Floor to sill heights are calculated based upon a structural header height of 6'-10 $\frac{1}{2}"$.